


Terminal Relay G6B-4CB

CSM_G6B-4CB_DS_E_4_1

Compact Terminal Relay with SPDT Relays and 4 Outputs

- Four G6B-2114P-US Relays mounted.
- LED operation indicator.
- Built-in diode absorbs coil surge.
- Special socket used for easy Relay replacement.
- Mounts either on DIN track or with screws.



Ordering Information

List of Models

Contact configuration	Coil terminal shape	Model	Rated voltage
Four SPDT relays	Phillips screw terminals	G6B-4CB	12 VDC
			24 VDC

Accessories (Order Separately)

Replacement Relays

Model	Rated voltage
G6B-2114P-US-P6B	12 VDC
	24 VDC

Specifications

Ratings

Coil Ratings (per G6B Relay)

Rated voltage (V)	Rated current (mA)	Coil resistance (Ω)	Must operate voltage (V)	Release voltage (V)	Max. voltage (V)	Power consumption (mW)
DC	12	27.0	80% max.	10% min.	110%	Approx. 300
	24	14.7				

- Note:**
1. Rated current and coil resistance were measured at a coil temperature of 23°C with a tolerance of $\pm 10\%$.
 2. Operating characteristics were measured at a coil temperature of 23°C.
 3. The rated current includes the terminal's LED current.

Contact Ratings (per G6B Relay)

Item	Load	Resistive load ($\cos\phi = 1$)	Inductive load ($\cos\phi = 0.4$, $L/R = 7$ ms)
Rated load		5 A at 250 VAC, 5 A at 30 VDC	1.5 A at 250 VAC, 1.5 A at 30 VDC
Rated carry current		5 A	
Max. switching voltage		250 VAC, 125 VDC	
Max. switching current		5 A	
Max. switching power (reference value)		1,250 VA, 150 W	375 VA, 45 W

■ Characteristics (per G6B Relay)


Contact resistance (See note 2.)	100 mΩ max.	
Must operate time (See note 3.)	10 ms max.	
Release time (See note 3.)	15 ms max.	
Insulation resistance	1,000 MΩ min. (at 500 VDC)	
Dielectric strength	1,000 VAC, 50/60 Hz for 1 min between contacts of same polarity	
	2,000 VAC, 50/60 Hz for 1 min between contacts of different polarity	
	2,000 VAC, 50/60 Hz for 1 min between coil and contacts.	
Vibration resistance	Destruction	10 to 55 to 10 Hz, 0.75 mm single amplitude (1.5 mm double amplitude)
	Malfunction	10 to 55 to 10 Hz, 0.75 mm single amplitude (1.5 mm double amplitude)
Shock resistance	Destruction	500 m/s ²
	Malfunction	100 m/s ²
Endurance	Mechanical	50,000,000 operations min. (at 18,000 operations/hr)
	Electrical (See note 3.)	100,000 operations min. (rated load) (at 1,800 operations /hr)
Minimum permissible load (reference value) (See note 4.)	5 VDC, 10 mA	
Ambient operating/storage temperature	-25 to 55°C (with no icing)	
Ambient operating humidity	45% to 85%	
Weight	Approx. 95 g	

- Note:**
1. The above values are initial values.
 2. Measurement condition: 1 A at 5 VDC
 3. Ambient temperature: 23°C
 4. This value is measured at 120 operations/min.


Engineering Data

■ Reference Data

Maximum Switching Power



Endurance




Note: Measurement values taken from production line samples have been plotted in graphs to provide this data. Use this data only as a guide. Relays are mass-produced, so allowances must be made for a certain amount of variation in measurement data.

Dimensions

Note: All units are in millimeters unless otherwise indicated.

Relays

G6B-4CB



Accessories (Order Separately)

Relay Removal Tool and Short Bar (Order Separately)

Refer to *Options for the G6B-4CB, G6B-4□□ND, and G3S4*.

Relay Mounting Products (Order Separately)

Safety Precautions

Refer to *Safety Precautions for All Relays*.

Precautions for Correct Use

When short-circuit wiring the NO, NC, or transfer contacts, be sure that the circuit configuration will not result in overcurrents or burnouts. The G6B-4CB uses G6B-2114P-US SPST-NO and SPST-NC contacts as the transfer contacts, which means there may be overlap when switching due to the asynchronous operation of the NO and NC contacts or arcs causing shorts between NO and NC contacts depending on the type of load.

ALL DIMENSIONS SHOWN ARE IN MILLIMETERS.

To convert millimeters into inches, multiply by 0.03937. To convert grams into ounces, multiply by 0.03527.

In the interest of product improvement, specifications are subject to change without notice.

Terms and Conditions Agreement

Read and understand this catalog.

Please read and understand this catalog before purchasing the products. Please consult your OMRON representative if you have any questions or comments.

Warranties.

(a) Exclusive Warranty. Omron's exclusive warranty is that the Products will be free from defects in materials and workmanship for a period of twelve months from the date of sale by Omron (or such other period expressed in writing by Omron). Omron disclaims all other warranties, express or implied.

(b) Limitations. OMRON MAKES NO WARRANTY OR REPRESENTATION, EXPRESS OR IMPLIED, ABOUT NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OF THE PRODUCTS. BUYER ACKNOWLEDGES THAT IT ALONE HAS DETERMINED THAT THE PRODUCTS WILL SUITABLY MEET THE REQUIREMENTS OF THEIR INTENDED USE.

Omron further disclaims all warranties and responsibility of any type for claims or expenses based on infringement by the Products or otherwise of any intellectual property right. (c) Buyer Remedy. Omron's sole obligation hereunder shall be, at Omron's election, to (i) replace (in the form originally shipped with Buyer responsible for labor charges for removal or replacement thereof) the non-complying Product, (ii) repair the non-complying Product, or (iii) repay or credit Buyer an amount equal to the purchase price of the non-complying Product; provided that in no event shall Omron be responsible for warranty, repair, indemnity or any other claims or expenses regarding the Products unless Omron's analysis confirms that the Products were properly handled, stored, installed and maintained and not subject to contamination, abuse, misuse or inappropriate modification. Return of any Products by Buyer must be approved in writing by Omron before shipment. Omron Companies shall not be liable for the suitability or unsuitability or the results from the use of Products in combination with any electrical or electronic components, circuits, system assemblies or any other materials or substances or environments. Any advice, recommendations or information given orally or in writing, are not to be construed as an amendment or addition to the above warranty.

See <http://www.omron.com/global/> or contact your Omron representative for published information.

Limitation on Liability; Etc.

OMRON COMPANIES SHALL NOT BE LIABLE FOR SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, LOSS OF PROFITS OR PRODUCTION OR COMMERCIAL LOSS IN ANY WAY CONNECTED WITH THE PRODUCTS, WHETHER SUCH CLAIM IS BASED IN CONTRACT, WARRANTY, NEGLIGENCE OR STRICT LIABILITY.

Further, in no event shall liability of Omron Companies exceed the individual price of the Product on which liability is asserted.

Suitability of Use.

Omron Companies shall not be responsible for conformity with any standards, codes or regulations which apply to the combination of the Product in the Buyer's application or use of the Product. At Buyer's request, Omron will provide applicable third party certification documents identifying ratings and limitations of use which apply to the Product. This information by itself is not sufficient for a complete determination of the suitability of the Product in combination with the end product, machine, system, or other application or use. Buyer shall be solely responsible for determining appropriateness of the particular Product with respect to Buyer's application, product or system. Buyer shall take application responsibility in all cases.

NEVER USE THE PRODUCT FOR AN APPLICATION INVOLVING SERIOUS RISK TO LIFE OR PROPERTY OR IN LARGE QUANTITIES WITHOUT ENSURING THAT THE SYSTEM AS A WHOLE HAS BEEN DESIGNED TO ADDRESS THE RISKS, AND THAT THE OMRON PRODUCT(S) IS PROPERLY RATED AND INSTALLED FOR THE INTENDED USE WITHIN THE OVERALL EQUIPMENT OR SYSTEM.

Programmable Products.

Omron Companies shall not be responsible for the user's programming of a programmable Product, or any consequence thereof.

Performance Data.

Data presented in Omron Company websites, catalogs and other materials is provided as a guide for the user in determining suitability and does not constitute a warranty. It may represent the result of Omron's test conditions, and the user must correlate it to actual application requirements. Actual performance is subject to the Omron's Warranty and Limitations of Liability.

Change in Specifications.

Product specifications and accessories may be changed at any time based on improvements and other reasons. It is our practice to change part numbers when published ratings or features are changed, or when significant construction changes are made. However, some specifications of the Product may be changed without any notice. When in doubt, special part numbers may be assigned to fix or establish key specifications for your application. Please consult with your Omron's representative at any time to confirm actual specifications of purchased Product.

Errors and Omissions.

Information presented by Omron Companies has been checked and is believed to be accurate; however, no responsibility is assumed for clerical, typographical or proofreading errors or omissions.